

Ringkern-Regeltransformatoren

Bestell-Nr.	Getrennte Wicklung	Spartransformator	Ohne Gehäuse	Mit Gehäuse	Labormodell	U_{prim}	U_{sec}	I_{nom}	I_{max}	Kerngrösse
2422 530 10407		X	X			220/230V	0-220/230V	0.5	0.6	E1.1
2422 530 11407		X	X			220/230V	0-220/230V	0.83	1	E2
2422 530 18407		X	X			220/230V	0-220/230V	1.4	1.7	E3
2422 530 03407		X	X			220/230V	0-260/272V	2	2.4	E4
2422 530 13407		X	X			220/230V	0-220/230V	2.5	3	E4
2422 530 90024		X	X			220/230V	0-220/230V	4	4.8	E5
2422 530 90028		X	X			220/230V	0-253/264V	4.5	5	E6
2422 530 04411		X		X		220/230V	0-260/272V	5	6	E6.1
2422 530 25411		X		X		220/230V	0-260/272V	8.5	11.2	E7
2422 530 04507		X	X			240V	0-270V	5	6.3	E6.1
2422 530 07507		X	X			240V	0-260V	23	30	E10
2422 530 90073		X	X			380/400V	0-380/400V	12	14.4	E10

weitere Typen auf Anfrage